

基本外形尺寸 (mm)				载荷 (kN)		极限转速 (rpm)		轴承型号	相关安装尺寸 (mm)			质量 (kg)
d	D	B	r _{1.2 min}	Cr	Cor	脂润滑	油润滑		d _{a min}	D _{a max}	r _{a max}	参考
						Grease	Oil					Refer.
100	140	40	1.1	194	400	950	2000	NNC4920V	106.5	133.5	1	2.00
100	140	40	1.1	194	400	950	2000	NNCL4920V	106.5	133.5	1	2.00
100	140	40	1.1	194	400	950	2000	NNCF4920V	106.5	133.5	1	2.00
100	150	67	1.5	391	680	950	2000	NNCF5020V	108	142	1.5	4.05
110	150	40	1.1	201	430	900	1900	NNC4922V	116.5	143.5	1	2.15
110	150	40	1.1	201	430	900	1900	NNCL4922V	116.5	143.5	1	2.15
110	150	40	1.1	201	430	900	1900	NNCF4922V	116.5	143.5	1	2.15
110	170	80	2	528	930	850	1800	NNCF5022V	119	161	2	6.60
120	165	45	1.1	224	480	800	1700	NNCF4924V	126.5	158.5	1	2.90
120	165	45	1.1	224	480	800	1700	NNC4924V	126.5	158.5	1	2.90
120	165	45	1.1	224	480	800	1700	NNCL4924V	126.5	158.5	1	2.90
120	180	80	2	561	1020	800	1700	NNCF5024V	129	171	2	7.10
130	180	50	1.5	255	530	750	1600	NNC4926V	138	172	1.5	3.90
130	180	50	1.5	255	530	750	1600	NNCL4926V	138	172	1.5	3.90
130	180	50	1.5	255	530	750	1600	NNCF4926V	138	172	1.5	3.91
130	200	95	2	704	1370	700	1500	NNCF5026V	139	191	2	11.0
140	190	50	1.5	264	570	700	1500	NNC4928V	148	182	1.5	4.15
140	190	50	1.5	264	570	700	1500	NNCL4928V	148	182	1.5	4.15
140	190	50	1.5	264	570	700	1500	NNCF4928V	148	182	1.5	4.16
140	210	95	2	737	1460	670	1400	NNCF5028CV	149	201	2	11.5
150	190	40	1.1	233	585	700	1500	NNC4830V	156.5	183.5	1	2.90
150	190	40	1.1	233	585	700	1500	NNCL4830V	156.5	183.5	1	2.90
150	210	60	2	380	850	670	1400	NNC4930V	159	201	2	6.70
150	210	60	2	380	850	670	1400	NNCL4930V	159	201	2	6.70
150	210	60	2	380	850	670	1400	NNCF4930V	159	201	2	6.71
150	225	100	2.1	842	1660	630	1300	NNCF5030V	161	214	2	14.0
160	200	40	1.1	242	620	670	1400	NNCF4832V	166.5	193.5	1	3.05
160	200	40	1.1	242	620	670	1400	NNC4832V	166.5	193.5	1	3.05
160	200	40	1.1	242	620	670	1400	NNCL4832V	166.5	193.5	1	3.05
160	220	60	2	396	900	630	1300	NNCF4932V	169	211	2	7.00
160	220	60	2	396	900	630	1300	NNC4932V	169	211	2	7.00
160	220	60	2	396	900	630	1300	NNCL4932V	169	211	2	7.00
160	240	109	2.1	968	1800	600	1200	NNCF5032V	171	229	2	17.0
170	215	45	1.1	264	655	630	1300	NNC4834V	176.5	208.5	1	4.10
170	215	45	1.1	264	655	630	1300	NNCL4834V	176.5	208.5	1	4.10
170	230	60	2	413	950	600	1200	NNC4934V	179	221	2	7.45
170	230	60	2	413	950	600	1200	NNCL4934V	179	221	2	7.45
170	230	60	2	413	950	600	1200	NNCF4934V	179	221	2	7.46
170	260	122	2.1	1140	2120	560	1100	NNCF5034V	181	249	2	23.0
180	225	45	1.1	270	695	600	1200	NNC4836V	186.5	218.5	1	4.30
180	225	45	1.1	270	695	600	1200	NNCL4836V	186.5	218.5	1	4.30
180	250	69	2	550	1220	560	1100	NNC4936V	189	241	2	10.5
180	250	69	2	550	1220	560	1100	NNCL4936V	189	241	2	10.5
180	250	69	2	550	1220	560	1100	NNCF4936V	189	241	2	10.6
180	280	136	2.1	1320	2500	560	1100	NNCF5036V	191	269	2	30.5
190	240	50	1.5	303	750	560	1100	NNC4838V	198	232	1.5	5.65
190	240	50	1.5	303	750	560	1100	NNCL4838V	198	232	1.5	5.65
190	260	69	2	561	1290	560	1100	NNCF4938V	199	251	2	11.0
190	260	69	2	561	1290	560	1100	NNCL4938V	199	251	2	11.0
190	290	136	2.1	1380	2600	530	1000	NNCF5038V	201	279	2	31.5
200	250	50	1.5	314	800	560	1100	NNC4840V	208	242	1.5	5.90
200	250	50	1.5	314	800	560	1100	NNCF4840V	208	242	1.5	5.91
200	280	80	2.1	660	1500	530	1000	NNC4940V	211	269	2	15.5
200	280	80	2.1	660	1500	530	1000	NNCF4940V	211	269	2	15.6
200	310	150	2.1	1570	3050	500	950	NNCF5040V	211	299	2	41.0
220	270	50	1.5	330	865	530	1000	NNC4844V	228	262	1.5	6.55
220	270	50	1.5	330	865	530	1000	NNCL4844V	228	262	1.5	6.55
220	270	50	1.5	330	865	530	1000	NNCF4844V	228	262	1.5	6.55
220	300	80	2.1	682	1600	500	950	NNCF4944V	231	289	2	17.0
220	300	80	2.1	682	1600	500	950	NNC4944V	231	289	2	17.0
220	300	80	2.1	682	1600	500	950	NNCL4944V	231	289	2	17.0
220	340	160	3	1870	3600	450	850	NNCF5044V	233	327	2.5	52.5
240	300	60	2	501	1290	480	900	NNC4848V	249	291	2	10.0
240	300	60	2	501	1290	480	900	NNCL4848V	249	291	2	10.0
240	300	60	2	501	1290	480	900	NNCF4848V	249	291	2	10.1
240	320	80	2.1	721	1760	450	850	NNC4948V	251	309	2	18.5
240	320	80	2.1	721	1760	450	850	NNCL4948V	251	309	2	18.5
240	320	80	2.1	721	1760	450	850	NNCF4948V	251	309	2	18.6
240	360	160	3	1980	3900	430	800	NNCF5048V	253	347	2.5	56.0

260	320	60	2	523	1400	430	800	NNC4852V	269	311	2	11.0
260	320	60	2	523	1400	430	800	NNCL4852V	269	311	2	11.0
260	320	60	2	523	1400	430	800	NNCF4852V	269	311	2	11.1
260	360	100	2.1	1080	2550	400	750	NNC4952V	271	349	2	32.0
260	360	100	2.1	1080	2550	400	750	NNCL4952V	271	349	2	32.0
260	360	100	2.1	1080	2550	400	750	NNCF4952V	271	349	2	32.1
260	400	190	4	2640	5200	380	700	NNCF5052V	276	384	3	85.5
280	350	69	2	682	1860	400	750	NNC4856V	289	341	2	16.0
280	350	69	2	682	1860	400	750	NNCL4856V	289	341	2	16.0
280	350	69	2	682	1860	400	750	NNCF4856V	289	341	2	16.1
280	380	100	2.1	1120	2700	380	700	NNC4956V	291	369	2	34.0
280	380	100	2.1	1120	2700	380	700	NNCL4956V	291	369	2	34.0
280	380	100	2.1	1120	2700	380	700	NNCF4956V	291	369	2	34.1
280	420	190	4	2700	5600	360	670	NNCF5056V	296	404	3	90.5
300	380	80	2.1	792	2120	380	700	NNCF4860V	311	369	2	23.0
300	380	80	2.1	792	2120	380	700	NNC4860V	311	369	2	23.0
300	380	80	2.1	792	2120	380	700	NNCL4860V	311	369	2	23.0
300	420	118	3	1540	3600	340	630	NNCF4960V	313	407	2.5	52.0
300	420	118	3	1540	3600	340	630	NNC4960V	313	407	2.5	52.0
300	420	118	3	1540	3600	340	630	NNCL4960V	313	407	2.5	52.0
300	460	218	4	3410	7100	320	600	NNCF5060V	316	444	3	130
320	400	80	2.1	825	2280	340	630	NNCF4864V	331	389	2	24.5
320	400	80	2.1	825	2280	340	630	NNC4864V	331	389	2	24.5
320	400	80	2.1	825	2280	340	630	NNCL4864V	331	389	2	24.5
320	440	118	3	1570	3800	320	600	NNCF4964V	333	427	2.5	55.0
320	440	118	3	1570	3800	320	600	NNC4964V	333	427	2.5	55.0
320	440	118	3	1570	3800	320	600	NNCL4964V	333	427	2.5	55.0
320	480	218	4	3470	7350	300	560	NNCF5064V	336	464	3	135
340	420	80	2.1	842	2400	320	600	NNCF4868V	351	409	2	25.5
340	420	80	2.1	842	2400	320	600	NNC4868V	351	409	2	25.5
340	420	80	2.1	842	2400	320	600	NNCL4868V	351	409	2	25.5
340	460	118	3	1610	4000	300	560	NNCF4968V	353	447	2.5	59.5
340	460	118	3	1610	4000	300	560	NNC4968V	353	447	2.5	59.5
340	460	118	3	1610	4000	300	560	NNCL4968V	353	447	2.5	59.5
340	520	243	5	4180	8800	280	530	NNCF5068V	360	500	4	185
360	440	80	2.1	880	2550	300	560	NNCF4872V	371	429	2	27.0
360	440	80	2.1	880	2550	300	560	NNC4872V	371	429	2	27.0
360	440	80	2.1	880	2550	300	560	NNCL4872V	371	429	2	27.0
360	480	118	3	1680	4150	300	560	NNCF4972V	373	467	2.5	61.0
360	480	118	3	1680	4150	300	560	NNC4972V	373	467	2.5	61.0
360	480	118	3	1680	4150	300	560	NNCL4972V	373	467	2.5	61.0
360	540	243	5	4290	9300	260	500	NNCF5072V	380	520	4	195
380	480	100	2.1	1300	3650	280	530	NNCF4876V	391	469	2	45.5
380	480	100	2.1	1300	3650	280	530	NNC4876V	391	469	2	45.5
380	480	100	2.1	1300	3650	280	530	NNCL4876V	391	469	2	45.5
380	520	140	4	2120	5400	260	500	NNCF4976V	396	504	3	91.5
380	520	140	4	2120	5400	260	500	NNC4976V	396	504	3	91.5
380	520	140	4	2120	5400	260	500	NNCL4976V	396	504	3	91.5
380	560	243	5	4400	9800	240	480	NNCF5076V	400	540	4	200
400	500	100	2.1	1320	3750	260	500	NNCF4880V	411	489	2	47.5
400	500	100	2.1	1320	3750	260	500	NNC4880V	411	489	2	47.5
400	500	100	2.1	1320	3750	260	500	NNCL4880V	411	489	2	47.5
400	540	140	4	2160	5700	240	480	NNCF4980V	416	524	3	95.5
400	540	140	4	2160	5700	240	480	NNC4980V	416	524	3	95.5
400	540	140	4	2160	5700	240	480	NNCL4980V	416	524	3	95.5
400	600	272	5	5500	12200	220	450	NNCF5080V	420	580	4	270
420	520	100	2.1	1340	4000	240	480	NNCF4884V	431	509	2	49.5
420	520	100	2.1	1340	4000	240	480	NNC4884V	431	509	2	49.5
420	520	100	2.1	1340	4000	240	480	NNCL4884V	431	509	2	49.5
420	560	140	4	2200	6000	220	450	NNCF4984V	436	544	3	99.5
420	560	140	4	2200	6000	220	450	NNC4984V	436	544	3	99.5
420	560	140	4	2200	6000	220	450	NNCL4984V	436	544	3	99.5
420	620	272	5	5150	11300			NNCF5084V	449	588	4	267
440	540	100	2.1	1400	4150	220	450	NNCF4888V	451	529	2	52.0
440	540	100	2.1	1400	4150	220	450	NNC4888V	451	529	2	52.0
440	540	100	2.1	1400	4150	220	450	NNCL4888V	451	529	2	52.0
440	600	160	4	2970	7500	200	430	NNCF4988V	456	584	3	137
440	600	160	4	2970	7500	200	430	NNC4988V	456	584	3	137
440	600	160	4	2970	7500	200	430	NNCL4988V	456	584	3	137
460	580	118	3	1540	4500	200	430	NNCF4892V	473	567	2.5	76.0
460	580	118	3	1540	4500	200	430	NNC4892V	473	567	2.5	76.0
460	580	118	3	1540	4500	200	430	NNCL4892V	473	567	2.5	76.0
460	620	160	4	3030	7650	190	400	NNCF4992V	476	604	3	140

460	620	160	4	3030	7650	190	400	NNC4992V	476	604	3	140
460	620	160	4	3030	7650	190	400	NNCL4992V	476	604	3	140
480	600	118	3	1570	4750	190	400	NNCF4896V	493	587	2.5	78.5
480	600	118	3	1570	4750	190	400	NNC4896V	493	587	2.5	78.5
480	600	118	3	1570	4750	190	400	NNCL4896V	493	587	2.5	78.5
480	650	170	5	3300	8300	180	380	NNCF4996V	500	630	4	165
480	650	170	5	3300	8300	180	380	NNC4996V	500	630	4	165
480	650	170	5	3300	8300	180	380	NNCL4996V	500	630	4	165
500	620	118	3	1610	4900	190	400	NNCF48/500V	513	607	2.5	81.5
500	620	118	3	1610	4900	190	400	NNC48/500V	513	607	2.5	81.5
500	620	118	3	1610	4900	190	400	NNCL48/500V	513	607	2.5	81.5
500	670	170	5	3360	8800	170	360	NNCF49/500V	520	650	4	175
500	670	170	5	3360	8800	170	360	NNC49/500V	520	650	4	175
500	670	170	5	3360	8800	170	360	NNCL49/500V	520	650	4	175
530	650	118	3	1680	5400	170	360	NNCF48/530V	543	637	2.5	85.0
530	650	118	3	1680	5400	170	360	NNC48/530V	543	637	2.5	86.0
530	650	118	3	1680	5400	170	360	NNCL48/530V	543	637	2.5	84.0
530	710	180	5	3910	10200	160	340	NNCF49/530V	550	690	4	200
530	710	180	5	3910	10200	160	340	NNC49/530V	550	690	4	200
530	710	180	5	3910	10200	160	340	NNCL49/530V	550	690	4	200